### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau



# 

(43) International Publication Date 17 June 2004 (17.06.2004)

PCT

## (10) International Publication Number WO 2004/051840 A1

(51) International Patent Classification7:

H02P 21/00

(21) International Application Number:

PCT/FI2003/000921

(22) International Filing Date: 2 December 2003 (02.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20022131

3 December 2002 (03.12.2002)

(71) Applicant (for all designated States except US): ABB OY [FI/FI]; Strömbergintie 15, FIN-00380 Helsinki (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): NHRANEN, Jouko [FI/FI]; Kylänevantie 2 A 4, FIN-00320 Helsinki (FI).

(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO utility model (BW), ARIPO patent (BW), ARIPO utility model (GH), ARIPO patent (GH), ARIPO utility model (GM), ARIPO patent (GM), ARIPO utility model (KE), ARIPO patent (KE), ARIPO utility model (LS), ARIPO patent (LS), ARIPO utility model (MW), ARIPO patent (MW), ARIPO utility model (MZ), ARIPO patent (MZ), ARIPO utility model (SD), ARIPO patent (SD), ARIPO utility model (SL), ARIPO patent (SL), ARIPO utility model (SZ), ARIPO patent (SZ), ARIPO utility model (TZ), ARIPO patent (TZ), ARIPO utility model (UG), ARIPO patent (UG), ARIPO utility model (ZM), ARIPO patent (ZM), ARIPO utility model (ZW), ARIPO patent (ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declarations under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA. CH. CN. CO. CR. CU. CZ. DE. DK. DM. DZ. EC. EE.

[Continued on next page]

METHOD FOR DEFINING QUADRATURE-AXIS MAGNETIZING INDUCTANCE OF SYNCHRONOUS (54) Title: **MACHINE** 



(57) Abstract: Method for defining quadrature-axis magnetizing inductance of a synchronous machine. the synchronous machine being supplied by an inverter. The method comprises steps, wherein the synchronous machine is started without load or with reduced load, the rotor current of the synchronous machine is kept substantially at zero, the synchronous machine is accelerated to initial angular velocity of measurement, the load angle (d<sub>s</sub>) of the synchronous machine is guided substantially to 90 degrees, the stator voltage  $(u_s)$ , the stator current  $(i_s)$  and

the electrical angular velocity (?) of the synchronous machine is defined and the quadrature-axis magnetizing inductance of the synchronous machine  $(l_{mo})$  is defined on the basis of the stator voltage  $(u_i)$ , the stator current (i,j) and the electrical angular velocity (?) of the machine.